

high quality ROAD COATING

ROADMARX PAINT

RoadMarx Paint is a superior high quality UV resistant direct to road coating. It is based on an acrylic copolymer emulsion. It is a high-performance water-based coating for road marking on bitumen and other surfaces.



ACRYLIC COPOLYMER EMULSION



LEAD
FREE



The product contains a flash rust inhibitor allowing for direct-to-metal application and has excellent adhesion qualities.



PRODUCT USES

- RoadMarx Paint is suitable for interior and exterior use on roads and floors.

PRODUCT ADVANTAGES

- It is quick drying, hard wearing and scratch resistant.
- Available in white, yellow, green and red.

COVERAGE

- Coverage is 8m² per liter depending on application method.
- Easy to clean off equipment with water, but once dry, a brush cleaner is recommended

PRODUCT USES

- Bitumen Road Surfaces
- Paved Parking Areas
- Sidewalks
- Floors
- School Playgrounds
- Cement / concrete surfaces

PRODUCT FEATURES

- Highly flexible.
- Water resistant.
- Excellent adhesion.
- UV resistant.
- Easy no-mess application.
- Quick-drying – 2 coats can be applied in one day.
- Direct application – no primer needed.
- Can be used as a base and top coat.

PRODUCT DATA

PHYSICAL FORM	Acrylic co-polymer
FINISH	Smooth sheen
COLOURS	White, Grey, Green, Red, Yellow, Black
THINNING	Not recommended – ready to use as is.
EQUIPMENT CLEANING	Water – do not allow the product to dry on equipment
FLASH POINT	Not applicable
SPREAD RATE	4m ² /L application at 125-150µm per coat. Coverage may vary depending on surface porosity and application method.
TOUCH DRY	+30min
MIXING	Always stir well before use with a flat paddle.

SURFACE PREPARATION (METALS)

Natural Stone, Concrete Cement, Plaster and Raw Wood Surfaces

- Remove dust, foreign material, fungal and algae growth with a heavy duty degreaser and rinse thoroughly with water, then allow to dry.
- Ensure that the surface is sound and dry before painting.
- If the surface is still dusty, apply a coat of a cement primer before applying the product.

PACKAGING

- RoadMarx Paint is available in 20L plastic drums.



APPLICATION



- Recommended thickness is 125 – 150 per applied coat – for best results 2 coats totalling 250 – 300 μm is recommended.

FOR BRUSH OR ROLLER APPLICATION

- Apply 1 or 2 coats of RoadMarx Paint at the recommended spread-rate of 4m²/L.
- Apply the first coat evenly, leave to dry for 30 to 60 minutes before applying the second coat, depending on the temperature.

FOR AIRLESS SPRAY APPLICATION

- Order the product spray-ready.
- Apply 1 or 2 coats of RoadMarx Paint at the recommended spread-rate of 4m²/L.
- Apply the first coat evenly, leave to dry for 30 to 60 minutes before applying the second coat, depending on the temperature.

SAFETY & HANDLING

- This product is non-flammable.
- Avoid contact with mouth and eyes.
- If body contact is made, rinse off immediately with water.
- Wear dust mask, gloves, eye protection and overalls when preparing surfaces and during application.
- Should the product come into contact with eyes, wash immediately with water and seek medical Advice.
- 6 to 12 months when stored in a cool, dry place or in a specifically constructed pumping station which is able to circulate the product correctly.
- Failure to comply with these recommendations may result in a reduction in the shelf life of the product.